



PNEUMATIC TYRED WHEELS

Wheel diam: 200mm - 400mm

Capacity: 65kg - 250kg

NB: Specify speeds anticipated when ordering. Please ask for recommendations as to your requirements.

Loading info: Low speed, manual propulsion only. Provides a cushioned ride for chemicals, instruments, suitable for outdoor trolleys & launching dollies.



TYRE DIAMETER mm	TREAD WIDTH mm	PLY RATING	CAPACITY KG	BORE DIAMETER	REFERENCE
STEEL CENTRE					
200	50	2	65	19	200-50PNSCR19
250	85	2	110	20	250-85PNSCB20
	85	6	130	25	250-85PNSCB25
300	85	2	110	20	300-85PNSCB20
	85	6	130	25	300-85PNSCB25
380	150	2	175	20	380-150PNSCB2
400	100	2	150	20	400-100PNSCB2
	100	6	200	25	400-10PNGCP25
	100	6	250	25	400-10PNGCR25
	100	6	250	25	400-10PNSCB25
	100	6	200	25	400-10PNSCP25
	100	6	250	25	400-10PNSCR25
NYLON CENTRE					
200	50	2	60	20	200-50PNNCP20
250	85	2	70	20	250-85PNNCP20
330	85	2	100	20	330-85PNNCP20
400	100	2	150	25	400-100PNNCP25

