



STANDARD INSTITUTIONAL CASTORS SINGLE BOLT HOLE FIXING

Pressed steel, electro zinc plated, double ball bearing swivel.

Available in:

2470 - Swivel

2475 - Wheel lock

2477 - Total lock



WHEEL DIA. mm	TREAD WIDTH mm	WHEEL TYPE	CAPACITY KG	OVERALL HEIGHT	BOLT HOLE	SWIVEL REF.	SWIVEL WITH WHEEL BRAKE REF.	SWIVEL WITH TOTAL BRAKE REF.
50	19	RUBBER P	40	70	10	2470PJ0050P30	2475PJ0050AP30	
		NYLON P	50		10	2470P00050P30	-	
75	25	RUBBER P	55	100	10	2470PJ0075P30	2475PJ0075P30	2477PJ0075P30
		NYLON P			10	2470P00075P30	-	
100	28	RUBBER R	80	134	12	2470PJR100P30	2475PJR100P30	2477PJR100P30
		NYLON P			12	2470P00100P30	-	
125	32	RUBBER R	100	159	12	2470PJR125P30	2475PJR125P30	2477PJR125P30
		NYLON P			12	2470P00125P30	-	

Wheel type - P=Plain bore, R=Roller bearing

FURNITURE FITTINGS & EXPANDING PLUGS



ROUND EXPANDERS	
TUBE INSIDE DIAMETER	REF.
19-21.5	R07/ 19-21.5
21.5-24	R07/ 21.5-24
24-27	R07/ 24-27
27-30	R07/ 27-30

SQUARE EXPANDERS	
TUBE INSIDE DIAMETER	REF.
21.5-24	R47/ 21.5-24
24-27	R47/ 24-27
27-30	R47/ 27-30



BED ROLLERS & GUIDES

DIAMETER	SPEC	REF.
50	ROLLER	3100POO 050B10-11
65	GLIDE	5899QOO 065B10-11

