



SOLID NYLON WHEELS

Wheel diam: 50mm - 200mm

Capacity: 55kg - 590kg

High deformation resistance, low abrasion resistance, runs fairly silently & is reasonably resistant to chemicals. Non marking shock resistant and gives fairly good floor protection. Suited to wet conditions, as uses water as a lubricant



WHEEL DIAMETER mm	TREAD WIDTH mm	CAPACITY KG	HUB		BORE DIAMETER	REF.
			LENGTH	DIA.		
50	18	55	27	14	6.4	W-050NY
65	22	90	33.5	19	9.5	W-065NY
75	25	125	38	28	12.7	W-075NY
100	31	225	44.5	28	14.3	W-100NY
125	35	270	49	28	14.3	W-125NY
150	38	500	60	36	19.05	W-150NY
200	38	590	60	49	19.05	W-200NY

PALLET ROLLERS

Fitted with sealed ball bearings. Used in low profile, high load capacity applications, e.g. Pallet Trucks



ROLLER DIAMETER mm	ROLLER WIDTH mm	CAPACITY KG	WHEEL TYPE	REF.
85	75	340	PU	085PT85X75FL
	95	385	PU	085PT85X95FL
	60	410	NY	085NY80X60FL
	70	410	NY	085NY80X70FL
	70	410	NY	085NY80X70CV
	95	410	NY	085NY85X95CV
	95	410	NY	085NY85X95FL

