

## SCAFFOLD CASTORS



**Wheel diam: 100mm - 200mm**

**Capacity: 225kg - 410kg**



WHEEL DIAMETER mm	TREAD WIDTH mm	CAPACITY KG	WHEEL TYPE	SWIVEL REFERENCE	SPIGOT DIA. mm x LENGTH
100	32	225	NYLON	C-100NYFG	32 x 125
150	38	410	NYLON	C-150NYFG	35 or 38 x 125
	40	370	PURETHANE	C-150PUFG	35 or 38 x 125
200	40	410	PURETHANE	C-200PUFG	35 or 38 x 125

## CAST IRON WHEELS

**Wheel diam: 75mm - 350mm**

**Capacity: 120kg - 2400kg**

High capacities, resists high & low temperatures, has low rolling resistance.

Heavy loads create high point loading and can damage floors. Ideal for low frequency movements & low speeds as metal does not deform.

Main application: Trolleys that stand for long periods, crane gantries & heavy duty working



WHEEL DIAMETER mm	TREAD WIDTH mm	CAPACITY KG	HUB		BORE DIA.	REF.	BEARINGS-ADD SUFFIX			
			LENGTH	DIA.			PLAIN	ROLLER	PRECISION BALL	TAPER ROLLER
75	35	120	39	25	12.7	W-075-35CW	P			
100	35	320	44	40	12.7	W-100-35CW	P			
	38	400	60	63	19.05	W-100-38CW	P	R		
150	45	910	60	63	25	W-150-45CW	P	R	B	
200	45	1100	60	63	25	W-200-45CW	P	R	B	
250	50	1200	60	70	25	W-250-50CW	P	R	B	
	75	2400	60	89	25	W-250-75CW	P	R	B	TR
300	50	1250	60	84	25	W-300-50CW	P	R	B	

